

4

3

2

1

2.00 X No. of Positions±0.20

2.00 X No. of Contacts-2.00±0.15

2.00 SQ0.50

2.00 X No. of Positions-4.00±0.15

0.80 2.00

P.C.B LAYOUT

不带柱

带柱

REVISION DATA

REV	DESCRIPTION	DATE
A0	NEW DRAWING	2011-04-21

Technical Data

Material:

Contact Material: Brass

Contact plating: Au or Sn Over 50μ" Ni

Insulator Material: Black Polyester UL94V-0

Standard: PA6T+30%G.F

Electrical:

Current rating: 2.0Amps/contact max.

Contact resistance: ≤20mΩ/contact

Insulation resistance: ≥1000MΩ at V=100V

Withstanding Voltage: 1000V AC/minute

Mechanical:

Mechanical life cycle: min.200

Operating temperature: -40°C to +105°C

Soldering temperature: +255°C

包装方式: 管装

Dimension antitheses list (尺寸选型表)

Item (项目)	L	W	PA	PB	H1	H2
Standard (尺寸)						
Remarks (备注)	以上尺寸可由客户选择					

PZ	2	XX	22	XXX	S	XX	C	X	N	XXX
品名 PZ=排针	间距 2=2.00	塑高 10=1.00mm 15=1.50mm 20=2.00mm	产品类型 22=双塑双排	PIN位总数 04~80P	产品折弯类型 S=3MT	表面处理 SN=1n120u" W=镀锌锡 G1=Gold 1u" G2=Gold 2u" G3=Gold 3u" G4=Gold 5u" G5=Gold 8u" G6=Gold 10u" G7=Gold 15u" G8=Gold 30u" GA=Gold 1.5u" S0=半金锡	塑胶材质 C=PA6T	塑胶特性 N=常规 W=带内柱	排针盖 N=无	针长 针长=(W-2.0)/2+D +PD+PA

**nicetycomm®** 深圳市创辉诚科技有限公司  
SHENZHEN CHUANGHUICHENG TECHNOLOGY CO.,LTD

TOLERANCE	PROJECTON	TITLE:
ANGLE ±5°	DATE: 2011-04-21	双排双塑SMT排针 PH2.00 系列图
X.XXX ±0.10	DRAWN:	PART NO: PZ2XX22XXXXXXCNXXX
X.XX ±0.20	CHECKED:	DRAWING NO: PZ2XX22SXXX039
X.X ±0.30	APPROVED:	REV: A0 UNIT: mm SCALE: 4:1 SIZE: A4
X. ±0.50		